

Standard delivery program

Tabelle dimensionali del programma di fornitura standard

CYLINDER TUBES EN 10305-1/2 - E355 +SR Tubi trafilati per cilindri EN 10305-1/2 - E355 +SR						
STOCK ALLOWANCE FOR HONING Sovrametalli per levigatura						
inside diameter mm	wall thickness mm					
	5,0	6,0	7,5	10,0	12,5	15,0
30,0						
35,0						
40,0						
45,0						
50,0						
55,0						
60,0						
63,0						
65,0						
70,0						
75,0						
80,0						
85,0						
90,0						
95,0						
100,0						
105,0						
110,0						
115,0						
120,0						
125,0						
130,0						
135,0						
140,0						
145,0						
150,0						
155,0						
160,0						
165,0						
170,0						
175,0						
180,0						
185,0						
190,0						
195,0						
200,0						

Inside diameter tolerance

<ul style="list-style-type: none"> -0,15/-0,30 -0,25/-0,45 -0,25/-0,55 	<ul style="list-style-type: none"> -0,30/-0,70 -0,50/-1,00
---	--

CYLINDER TUBES EN 10305-1/2 - E355 +SR Tubi trafilati per cilindri EN 10305-1/2 - E355 +SR						
STOCK ALLOWANCE FOR SKIVING AND ROLLER BURNISHING Sovrametalli per pelatura e rullatura						
inside diameter mm	wall thickness mm					
	5,0	6,0	7,5	10,0	12,5	15,0
30,0						
35,0						
40,0						
45,0						
50,0						
55,0						
60,0						
63,0						
65,0						
70,0						
75,0						
80,0						
85,0						
90,0						
95,0						
100,0						
105,0						
110,0						
115,0						
120,0						
125,0						
130,0						
135,0						
140,0						
145,0						
150,0						
155,0						
160,0						
165,0						
170,0						
175,0						
180,0						
185,0						
190,0						
195,0						
200,0						

Inside diameter tolerance

<ul style="list-style-type: none"> -0,30/-0,55 -0,40/-0,70 -0,50/-0,85 	<ul style="list-style-type: none"> -0,50/-0,90 -0,60/-1,20
---	--